FRKPV-DS-01-MTLH C & I DISCLAIMER

FRKPV-PJ-01-MTLH EXPANDED PANEL JOINT FRKPV-PJ-02-MTLH ENGAGED PANEL JOINT FRKPV-PJ-03-MTLH INTERMEDIATE SUPPORT

FRKPV-FS-01-MTLH MULTI-STORY FIRE STOPPING DETAIL FRKPV-FS-02-MTLH MULTI-STORY FIRE STOPPING ASSEMBLY

FRKPV-BS-01-MTLH BASE DETAIL FLUSH

FRKPV-BS-02-MTLH BASE AT NOTCHED CONCRETE

FRKPV-BS-03-MTLH BASE AT OVERHANG FRKPV-BS-04-MTLH BASE AT OVERHANG FRKPV-OC-01-MTLH OUTSIDE CORNER INSIDE CORNER

FRKPV-FO-01-MTLH FRAMED OPENING HEAD FRKPV-FO-02-MTLH FRAMED OPENING JAMB FRKPV-FO-03-MTLH FRAMED OPENING SILL

FRKPV-SJ-01-MTLH STACK JOINT

FRKPV-PR-01-MTLH PARAPET DETAIL FRKPV-LE-01-MTLH LOW EAVE DETAIL

FRKPV-RD-01-MTLH RAKE DETAIL

FRKPV-TP-01-MTLH PANEL TERMINATION

FRKPV-TL-01-MTLH TRIM END LAP

FRKPV-TL-02-MTLH TRIM END LAP WITH HEMS

INDEX SHEET

DETAIL #: FRKPV-XX-XX-MTLH



#### DISCLAIMERS:

THESE DETAILS ARE PROVIDED AS A GUIDELINE FOR PROPER PANEL AND ASSOCIATED COMPONENT INSTALLATION, AND ARE BASED ON INDUSTRY ACCEPTED PRACTICES.

LOCATION OF VAPOR BARRIERS AND ASSOCIATED SEALANTS IN THESE DETAILS ARE BASED ON TYPICAL DESIGN PRACTICES FOR MOST U.S. AND CANADIAN CLIMACTIC ZONES. (THE PRIMARY VAPOR BARRIER IS PLACED ON THE "WARM" SIDE IN WINTER).

PROJECTS LOCATED IN AREAS SUBJECT TO EXTREME COLD AND/OR HIGH SNOW LOADS MAY REQUIRE MODIFICATIONS TO THESE DETAILS - CONTACT KINGSPAN TECHNICAL SERVICES FOR SPECIFIC PROJECT RECOMMENDATIONS.

ALL STRUCTURAL SUPPORTS ARE NOT BY KINGSPAN AND ARE SHOWN FOR CLARIFICATION AND ILLUSTRATION PURPOSES ONLY.

WALL SYSTEM DEFLECTIONS ARE TO BE DETERMINED BY THE ENGINEER OF RECORD.

ALL STRUCTURAL SUPPORTS ARE NOT BY KINGSPAN AND ARE SHOWN FOR CLARIFICATION AND ILLUSTRATION PURPOSES ONLY.

CONTACT KINGSPAN TECHNICAL SERVICES FOR MAXIMUM ALLOWABLE PANEL SPANS AND FASTENING PATTERNS.

**DISCLAIMER** 

DETAIL #: FRKPV-DS-01-MTLH



<u>CORE DEPTHS:</u> 2", 2.5", 3", 4", 5", 6"

MODULE WIDTH: 24", 30", 36", 42"

EMBOSSING: EXTERIOR: STUCCO / SMOOTH\* INTERIOR: STUCCO / SMOOTH


LENGTHS:


PANEL ORIENTATION: VERTICAL


STEEL GAUGES: EXTERIOR: (REFER TO PROFILE) INTERIOR: 26, 24, 22


REVEAL: %"
KARRIER CONFIGURATION
REQUIRES %" REVEAL

MINIMUM: 8'-0" MAXIMUM: 53'-0"









EXPANDED PANEL JOINT

DETAIL #: FRKPV-PP-01-MTLH



<u>CORE DEPTHS:</u> 2", 2.5", 3", 4", 5", 6"

MODULE WIDTH: 24", 30", 36", 42" PANEL ORIENTATION: VERTICAL

EXTERIOR: STUCCO / SMOOTH\*
INTERIOR: STUCCO / SMOOTH

LENGTHS:


**STEEL GAUGES:** 


EXTERIOR: (REFER TO PROFILE)

INTERIOR: 26, 24, 22

MINIMUM: 8'-0" MAXIMUM: 53'-0"

**EMBOSSING:** 






EXPANDED PANEL JOINT

DETAIL #: FRKPV-PP-01-MTLH



#### NOTE:

FOR PROJECTS REQUIRING NFPA 285: INTERIOR SIDE OF FRAMING MUST HAVE %" THICK FIRE BLOCK TYPE X GYPSUM BOARD (NOT BY KINGSPAN)




SEE NEXT DETAIL FOR FACADE FASTENING DETAILS

WALL PANEL INSTALLATION DIRECTION — -

EXPANDED PANEL JOINT

DETAIL #: FRKPV-PJ-01-MTLH






ENGAGED PANEL JOINT

DETAIL #: FRKPV-PJ-02-MTLH

DATE: 2019



INTERMEDIATE SUPPORT

DETAIL #: FRKPV-PJ-03-MTLH

DATE:


2019



# VERTICAL KARRIER™ PANEL - FLAT RAIL - METAL FACADE NOTE: FOR PROJECTS REQUIRING NFPA 285: INTERIOR SIDE OF FRAMING MUST HAVE %" THICK FIRE BLOCK TYPE X KARRIER PANEL GYPSUM BOARD (NOT BY KINGSPAN) INSTALLED **VERTICALLY** FASTENING AND OTHER MATERIALS NOT SHOWN FOR CLARITY OF **DETAIL FACADE PANEL** FLOOR SLAB, FRAMING (INSTALLED AND OTHER MATERIALS **VERTICALLY**) (NOT BY KINGSPAN) COMPLETELY FILL VOID BETWEEN **INSULATION WASHER** INSULATED METAL PANEL SYSTEM AND FASTENERS @ AND FACADE WITH MIN 4PSI 12" O.C. CONTINUOUS FIRE BLOCKING AT (NOT BY KINGSPAN) **EACH FLOOR LINE** (NOT BY KINGSPAN) VOID DETAIL #: FRKPV-FS-01-MTLH **MULTI-STORY FIRE**

MULTI-STORY FIRE STOPPING DETAIL






MULTI-STORY FIRE STOPPING ASSEMBLY

DETAIL #: FRKPV-FS-02-MTLH

DATE: 2019

#### NOTE:

FOR PROJECTS REQUIRING NFPA 285: INTERIOR SIDE OF FRAMING MUST HAVE 5/8" THICK FIRE BLOCK TYPE X GYPSUM BOARD (NOT BY KINGSPAN)




BASE DETAIL FLUSH

DETAIL #: KPH-BS-01-MTLV



#### NOTE:

FOR PROJECTS REQUIRING NFPA 285: INTERIOR SIDE OF FRAMING MUST HAVE 5/8" THICK FIRE BLOCK TYPE X GYPSUM BOARD (NOT BY KINGSPAN)




BASE AT NOTCHED CONCRETE

DETAIL #: FRKPV-BS-02-MTLH



#### NOTE:


FOR PROJECTS REQUIRING NFPA 285: INTERIOR SIDE OF FRAMING MUST HAVE 5/8" THICK FIRE BLOCK TYPE X GYPSUM BOARD (NOT BY KINGSPAN)



BASE AT OVERHANG

DETAIL #: FRKPV-BS-03-MTLH






BASE ANGLE W/ MINIMUM 3" VERT. LEG FOR PANEL ATTACHMENT SET IN SEALANT (NOT BY KINGSPAN)

CONTINUOUS BUTYL SEALANT BELOW BASE FLASHING

BASE AT OVERHANG

DETAIL #: FRKPV-BS-04-MTLH






**OUTSIDE CORNER** 

DETAIL #: FRKPV-OC-01-MTLF


DATE: 2019



**INSIDE CORNER** 


DETAIL #: FRKPV-IC-01-MTLH


DATE: 2019



FRAMED OPENING HEAD DETAIL #: FRKPV-FO-01-MTLH








FRAMED OPENING JAMB DETAIL#: FRKPV-FO-02-MTLH






FRAMED OPENING SILL

DETAIL #: FRKPV-FO-03-MTLH






STACK JOINT

DETAIL #: FRKPV-SJ-01-MTLH


DATE: 2019



PARAPET DETAIL

DETAIL #: FRKPV-PR-01-MTLH






LOW EAVE DETAIL

DETAIL #: FRKPV-LE-01-MTLH






RAKE DETAIL

DETAIL #: FRKPV-RD-01-MTLH






PANEL TERMINATION

DETAIL #: FRKPV-TP-01-MTLH






TRIM END LAP

DETAIL #: FRKPV-TL-01-MTLH





TRIM END LAP WITH HEMS

DETAIL #: FRKPV-TL-02-MTLH

