PROVISIONS BY OTHERS PLAN VIEW - ZENITH AUTO SLIM DOOR RESIDENTIAL-3654 (1R) SECTIONAL VIEW - ZENITH AUTO SLIM DOOR RESIDENTIAL - 3654 (1R) *GENERAL HOISTWAY- THE HOISTWAY MUST BE IN ACCORDANCE WITH CIDITS WHIT— THE HOLSTWAY MUST BE IN ACCORDANCE WITH "SAFETY CODE FOR ELEVATORS AND ESCALATORS" (ASME A17.1) AND ALL STATE AND LOCAL CODES. PLINB HOLSTWAY— DUE TO CLOSE RUNNING CLEARANCES OWNER/AGENT HUST ENSURE THAT HOLSTWAY AND PIT CYHERE PROVIDED) ARE LEVEL, PLUMB AND SQUARE AND ARE IN ACCORDANCE VITH THE DIMENSIONS ON THESE DRAWINGS. -L/B LOCATED IN THE H/W CEILING 64 1/8" [1629mm] FINISHED RUNWAY LENGTH UNICHAILES UN TEST INTERNATIONS. HINCHIA DVERHEAD CLEARANCE IS IN COMPLIANCE WITH CODES. CONSTRUCTION SITE— OWNER/AGENT TO PROVIDE ALL MASONRY, CARPENTRY AND DRYWALL WORK AS REQUIRED AND SHALL PATCH AND MAKE GOOD (INCLUDING FIRISH PAINTUNG) ALL AREAS WHERE WALLS/FLOORS HAY REQUIRE TO BE CUT, DRILLED OR ALTERED [N ANY WAY TO PERMIT THE PROPER INSTALLATION OF THE LIFT. 3 1/2" [89nn] --RUNNING CLEARANCE 54" [1372mm] CLEAR CAB DEPTH DIMENSIONS CONTRACTOR/CUSTOMER TO VERDEY ALL DIMENSIONS AND REPORT ANY 34 1/2" [876mm] DBG -DISCREPANCIES TO OUR OFFICE IMMEDIATELY E RAIL BRKT *STRUCTURAL #STRUCTIONS AND ALL LOADS—STRUCTURE TO ANCHOR A CRANK SHAFT AND SAFETY HARNESS, WHERE APPLICABLE/NECIED, TO BE PROVIDED BY CONTRACTOR. CONTRACTOR TO ASSURE THAT BUILDING AND SHAFT WILL SAFELY SUPPORT ALL LOADS DIPOSED BY THE LIFT EQUIPMENT, REFER TO THE TABLES ON THIS DRAWING FOR LOADS (MPOSED BY THE EQUIPMENT. LIFTING BEAM NIN SVL 400016 — 31" [787mm] *MACHINE ROOM (WHERE REQUIRED) LOCATION / ACCESS - MACHINE ROUN LOCATED AT THE LOWEST LEVEL ADJACENT TO HOISTWAY, UNLESS SHOWN OTHERWISE ON THE LAYOUT DRAWDINGS, FIELD ADJUSTMENT BY INSTALLER MAY BE RECESSARY TO MEET JOB SITE CONDITIONS OR REGULATIONS, MACHINE ROON DOOR IS TO BE LOCKABLE AND IS TO MEET THE REQUIREMENTS OF THE AUTHORITY HAVING JURISDICTION. SLEFVES FOR FLECTRIC LINES - FROM MACHINE ROOM TO HOISTWAY AS REQUIRED, (POSITION PER INSTALLERS INSTRUCTIONS). ICSCONNECT TIME DELAY SIZE FUSE SIZE VOLLTS PHASE NOTOR & EQUIP 30 ANPS 30 AMPS 208 valt Three Phase 28.9 ANPS MOTOR & EQUIP 60 AMPS 40 AMPS 230 volt Single Phase 35.0 AMPS CAB LIGHTS 15 AMPS 15 AMPS 115 V Single Phase POWER SLPPLY— (SEE SPECIFICATIONS) LOCKABLE FUSED DISCONNECT WITH AUXILIARY CONTACT TO BRAKE THE DATTERY FEED, OR CIRCUIT BREAKERS WITH A 3-POLE BREAKER FOR DATTERY FEED REQUIRED, IN COMPLIANCE WITH A LECTRICAL COME, AS FOLLOWS. CLOCATED ON WALL ON LOCK JAKE SIDE OF MACHINE ROOM DOOR) • ÷ • 6 $\underline{\text{PERNANENT POWER}}$ BEFORE INSTALLATION CAN BEGIN, PERMANENT POWER MUST BE SUPPLIED. LIGHTING— THE ILLUMINATION SHALL BE NOT LESS THAN 200 LX (19 FC) AT THE FLOOR LEVEL IN ALL MACHINE ROOMS AND MACHINERY SPACES. ENSURE AT LEAST 100 LX (10 FC) AMBIENT LIGHTING OVER LIFT AREA. PHONE - NEED A DEDICATED PHONE LAND LINE <u>-</u> + - | □ RAI RAI FASCIA PANEL BELIOV UPPER LEVEL ENTRANCE— WHERE REQUIRED, FASCIA PANEL MUST BE FASTENED TO A SOLID VALL AND BE PERPENDICULAR TO THE FLOOR AND WALLS. HOISTWAY FASCIA SUT SELF-SUPPORTING FOR LONG, CONTINUOUS RUNS VOID OF ENTRANCES, ALEQUATE SUPPORT FOR THE FASCIA MUST BE PROVIDED. NOTE LIFTING BEAM A 4000LB MON SWL BEAM MUST BE PROVIDED IN THE OVERHEAD, BEAM TO BE POSITIONED AS SHOWN IN ELEVATION & PLAN VIEWS, FOR OVERHEAD OF 108", POSITION THE UNDERSIDE OF BEAM AT 104" & BEAM MLST BE TEMPORARY. 14 45 6 A STATE OF THE STA -32 1/4" [819nm] -R3 LDAD ON BUFFERS R48R5 LDAD ON RAGES OVERSPEED GOVERNOR TO SAFETY BRAKE ON SLING NOTE C ⊞^{R3} R3⊞ ALL INFORMATION IS SUBJECT TO CHANGE. PLEASE REFERENCE DUR ON-LINE DRAWINGS AT 0 www.savaria.com FOR THE MOST RECENT UPDATES **₩**₩ R3 ∰= ENTRANCE — 5 3/8″ [136mm] 11 3/16" [284mm] --HALL BUTTON NEEDED 3/1 RAIL BRACKETS AT ALL FLOORS TABLE 2 RAIL BRACKETS PIT RE-ACTION FORCE 2"X4" [51X102mm] RЭ 8000 LBS ELECTRICAL BOX 3000 LBS R4 RAIL FORCES 9500 LBS R5 LOADS ON PIT * R2 **≭**R1 500 lbf 1570 lbf RESIDENTIAL ELEVATOR (503) RAIL WEIGHT | 8.0 lbs / ft ZENITH MODEL 36X54 TYPE 1R FOR TOTAL PULL-OUT FORCE ON RAIL BRACKET, LEFT HAND SHOWN eq.2 x 720 = 1440 lbf CUSTOMER FOR LOCAL APPLICATION OF PIT LOAD, THE SHERWITCH COCKLOSES HEREDI IS THE EXCLUSIVE PROPERTY OF RIGHT HAND OPPOSITE RI HUST BE COUBLED. TOPATION COMPLETED :

WO HAY HOT BE USED BY ITHERS VITIOUT PRIOR VROTTED CORRECT