

PENETRATIONS, MEMBRANE, FLASHING AND METAL DAM (INSIDE POCKET) MUST BE PRIMED PRIOR TO APPI YING POURABLE SEALER.

SURE-SEAL PRESSURE-SENSITIVE POURABLE SEALANT POCKET

**INSULATION** 

SURE-SEAL<sup>®</sup>/SURE-WHITE<sup>®</sup> EPDM MEMBRANE

## NOTES:

- 1. 180° F (82° C) MAXIMUM TEMPERATURE.
- 2. POURABLE SEALER MUST CONTACT PRIMED PRESSURE-SENSITIVE ELASTOFORM FLASHING AND DECK MEMBRANE.
- 3. POURABLE SEALER POCKET TO BE 1" (25 mm) MINIMUM FROM PENETRATION ON ANY SIDE.
- 4. POURABLE SEALER MUST COMPLETELY FILL POURABLE SEALER POCKET TO PREVENT PONDING OF WATER.
- 5. SECUREMENT IS REQUIRED FOR POURABLE SEALER POCKETS WHICH ARE GREATER THAN 18" (500 mm) IN DIAMETER. REFER TO SPECIFICATIONS.
- 6. POURABLE SEALER TO BE MINIMUM 2" (50 mm) DEEP.
- 7. ALL DEBRIS (PAINT, RUST, LEAD, OTHER FLASHINGS, ETC.) MUST BE REMOVED FROM THE PENETRATION.
- 8. FOR ADDITIONAL INFORMATION, REFER TO SURE-SEAL POURABLE SEALER POCKET INSTALLATION INSTRUCTIONS IN THE MISCELLANEOUS SECTION.
- 9. ON MECHANICALLY-FASTENED ROOFING SYSTEMS, ADDITIONAL MEMBRANE SECUREMENT IS REQUIRED. REFER TO SPECIFICATIONS.

PS-16-F

SURE-SEAL® PRESSURE-SENSITIVE POURABLE SEALER POCKET

