

Skylights conform to and exceed test requirements of CAN/CGSB-63.14M89, "Plastic Skylights", Class A, Type 2 or Type 3.

Skylights are suitable for use on flat roofs only. Designed for mounting on 3"(75mm) or 4"(102mm) curbs with flashing (by others), these units provide excellent performance and flexible design to achieve large daylight openings.

- Custom sizes are available upon request



Model CU-FF-DE Available Sizes			
Model #	Outside Curb Dimensions	Glazing Color	QTY
CU-FF-DE 36	33½" x unlimited (845mm x unlimited)		
CU-FF-DE 42	40" x unlimited (1016mm x unlimited)		
CU-FF-DE 52	49¼" x unlimited (1251mm x unlimited)		
CU-FF-DE 60	58" x unlimited (1473mm x unlimited)		
CU-FF-DE 72	70" x unlimited (1778mm x unlimited)		
CU-FF-DE 80	78" x unlimited (1981mm x unlimited)		
CU-FF-DE 96	92½" x unlimited (2350mm x unlimited)		
CU-FF-DE CUST.			
CU-FF-DE CUST.			
Glazing Colors Available			
Glazing Color	Colour Code	Glazing Color	Colour Code
Clear	- C	White	- W
Bronze	- B	Grey	- G

Project:
Contractor:
Architect:
Approved By:
Date:

Specifications:

Skylight shall be factory assembled Model No. _____ CU-FF-DE as manufactured by Artistic Skylight Domes Ltd. Etobicoke, Ontario. Glazing shall consist of, double acrylic dome ends and curved centre drapes of clear, white, bronze, or grey (when available). The skylight shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corner. The skylight curb frame shall have an extruded rigid vinyl thermal break, which incorporates a high capacity, sloped condensation gutter with drainage to exterior, and co-extruded rubber draft seal. The retaining cap frame shall be extruded, mill finish, 6063-T5 aluminum alloy with heliarc welded corners. Mullions shall consist of 3" mill finish, pre-arc'd, extruded aluminum channel and pressure plate of 6063-T5 alloy, with keyed in place Santoprene gaskets and spacers. Channel spacing approximately 4' on centre. For units smaller than 5' wide, replace 3" Channel with 3" Flat Channel.

