

Insulating glazing units conform to and exceed test requirements of CAN/CGSB-12.8-M90 and IGMAC certification program.

Skylights are suitable for use on flat roofs, for mounting on curbs and flashing by others. Provides flexibility to obtain openings by joining two or more skylights in grid format.

Custom sizes are available upon request



Model G-FF-BUTTED Available Sizes				
Model #	Centerline Dimensions		Glass Glazing Type	QTY
G-FF-BUTTED 3636	33 $\frac{3}{4}$ " x 33 $\frac{3}{4}$ "	(845mm x 845mm)		
G-FF-BUTTED 4242	40" x 40"	(1016mm x 1016mm)		
G-FF-BUTTED 5252	49 $\frac{1}{4}$ " x 49 $\frac{1}{4}$ "	(1251mm x 1251mm)		
G-FF-BUTTED 6060	58" x 58"	(1473mm x 1473mm)		
G-FF-BUTTED 7272	70" x 70"	(1778mm x 1778mm)		
G-FF-BUTTED 9696	92 $\frac{1}{2}$ " x 92 $\frac{1}{2}$ "	(2350mm x 2350mm)		
G-FF-BUTTED CUST.				
G-FF-BUTTED CUST.				
Glass Colors Available				
Dome Color	Colour Code	Glass Glazing	Colour Code	
Clear/Low-E	- Low-E	Clear/Laminated	- Lami.	
Bronze/Low-E	- B/Low-E	Argon/Low-E	- Low-E/Arg	
Project:				
Contractor:		Approved By:		
Architect:		Date:		

Specifications:

Skylight shall be factory assembled Model No. _____ G-FF-BUTTED as manufactured by Artistic Skylight Domes Ltd. Vaughan, Ontario. Glazing shall consist of, sealed dual tempered glass of clear low-E over clear. The skylight shall consist of corrosion resistant extruded aluminum curb frame, 6063-T5 alloy, with heliarc welded corners. The skylight curb frame shall have an extruded rigid vinyl thermal break (to prevent thermal transfer to interior of building) which incorporates a high capacity, 5 degree sloped condensation gutter with drainage to exterior, and co-extruded rubber draft seal. The retaining cap frame shall be extruded, mill finish (optional baked enamel), 6063-T5 aluminum alloy with heliarc welded corners.

