## METALWRAP-H W/MR-100 PLASTER CORNER ACCESSORY INTERIOR SIDE -MEMBRANE FLASHING; APPLY A CURING BUTYL CONTINUOUS TO BASE. SEALANT PLUG NEAR EACH NOTCH PANEL LINER AT PANEL END DURING PANEL CORNERS AS SHOWN -ERECTION. (PROVIDES A THERMAL (SEE DETAIL BELOW) BREAK) 4" X 4" 20GA GALV. ANGLE SEALANT BETWEEN PANEL LINER AND . INTERIOR MEMBRANE 9" WIDE EXTERIOR SIDE MEMBRANE OR METAL -STEEL STUD FLASHING: CONTINUOUS 18 GA. MIN. ONTO BASE FLASHING BELOW. 7/8" 3-COAT CEMENT-PLASTER SYSTEM 0/ INTERIOR SELF-FURRING, GALV. **GYPSUM** METAL LATH BOARD METALWRAP PANEL; -MINIMUM SEALANT -FIELD CUT AS REQ'D CONTACT SHOWN 3/4" HAT CHANNEL @ 16" -O.C., MAX. Ż CONTINOUS METALWRAP PANEL RAIL AT EACH PANEL SIDE -<u>%</u> JOINT (36" O.C.) VERTICALLY AND FÄSTENED INTO EACH FRAMING MEMBER (16" TO 24" O.C.) HORIZONTALLY FLASHING TAPE SEALANT PLUG DETAIL APPLY SEALANT AS PANELS ARE ERECTED. Outside 90° Corner w/ 3-Coat Plaster **CENTRIA** METALWTAD



MW100-09P