## HORIZONTAL METALWRAP - MASONRY SHOP APPLIED 2" AIR CAVITY AIR/VAPOR BARRIER (1" OPTIONAL) -SEALANT METALWRAP INSULATED BACK-UP PANEL-HOHMANN AND BARNARD-JOINT CLIP AND MASONRY STEEL STUD ANCHOR AT EACH PANEL 18 GA. MIN. SIDE JOINT (32" O.C.) VERTICALLY AND INTO FIELD CUT EACH FRAMING MEMBER PANEL (16" TO 24" O.C.) AS REQUIRED HORIZONTALLY PRIMARY MEMBRANE FLASH -**MEMBRANE** LOCATE AT EACH FLASHING FROM VERTICAL PANEL JOINT ABOVE WINDOW WINDOW PERIMETER HOHMANN AND BARNARD -TO PANEL LINER FACE CLIP AND MASONRY ANCHOR AS REQ'D (AT SEALANT MINIMUM 12" FROM BETWEEN **MEMBRANE** OPENING). FLASH AND TERMINATION BAR PANEL LINER SEALANT AND FASTENER AT WINDOW HEADER MEMBRANE FLASHING PER STEEL (NBC-BY MASON) DESIGN MORTAR NET -WOOD BLOCKING (NBC-BY MASON) PANEL THRU-FASTENER -INTERIOR WITH 3"x3" FLEXIBLE GYPSUM MEMBRANE SEAL \* BOARD WEEP/VENTS : AT 24" O.C. (NBC-BY MASON) WINDOW ROOM PRIMARY SEAL FLEXIBLE MEMBRANE FLASHING WITH STAINLESS (BY WINDOW STEEL DRIP FLASH CONTRACTOR) OFFSET FOR FOR TO INSERT SI SET IN SEALANT (NBC) WINDOW SECONDARY LINTEL ANGLE-SEAL (BY (BY OTHERS) OTHERS) SEALANT -WINDOW AND (BY OTHERS) PANNING (BY OTHERS) **METALWI'AD** Window Head MR200-04 JANUARY 2018