

METALWRAP LONGSPAN

INTERIOR SIDE
MEMBRANE FLASHING;
CONTINUOUS TO BASE.

NOTCH PANEL LINER AT
CORNERS AS SHOWN
(PROVIDES A THERMAL
BREAK)

SEALANT BETWEEN
PANEL LINER AND
INTERIOR MEMBRANE

9" WIDE EXTERIOR SIDE
MEMBRANE OR METAL
FLASHING; CONTINUOUS
ONTO BASE FLASHING
BELOW.

CSC-3 FLUSH
PANEL CLIP

1½" SUBFRAMING
AND AIR CAVITY

CONCEPT SERIES
CS-260 PANEL
(MITERED CORNER)

METALWRAP PANEL;
FIELD CUT AS REQ'D

CSC-3 FLUSH
PANEL CLIP
w/INVERTED HAT

APPLY A CURING BUTYL
SEALANT PLUG NEAR EACH
PANEL END DURING PANEL
ERECTION.
(SEE DETAIL BELOW)

SUPPORTS
(NBC)

2¾"

NOTE:
THESE DETAILS ARE FOR INSTALLATION
AND SEALING OF METALWRAP PANELS
ONLY. FOR INSTALLATION AND SEALING
REQUIRED FOR FACE PANELS SEE CENTRIA
STANDARD DETAILS FOR THE SPECIFIC
FACE PANEL.



METALwrap

Outside 90° Concept Series Mitered Corner
MWLS100-09A

JANUARY 2018