



PARTS DESCRIPTION

- ① #12 x 2" S.S. WITH SECURITY TIP & CSK WASHER
4" FROM EACH END & 12" O.C FOR STANDARD SYSTEM.
6" O.C FOR THE HIGH CRIME SYSTEM.
- ② #12 x 1" S.S. WITH SECURITY TIP
3" FROM EACH END & 12" O.C. FOR STANDARD SYSTEM.
6" O.C. FOR THE HIGH CRIME SYSTEM.
REQUIRES 1/4" HOLE DRILLED IN .236 DEFENSELITE.
- ③ 1" WIDE HIGH BOND TAPE
1" TUBE TO EXISTING FRAMING.
- ④ 3/4" WIDE HIGH BOND TAPE
1" TUBE TO NEW .236 DEFENSELITE.
- ⑤ 3/4" WIDE HIGH BOND TAPE
NEW 1" FLAT BAR TO NEW .236 DEFENSELITE.
- ⑥ 1" x 1" x .063 (6063) ALUM. TUBE
1" x 1" x .125 (6063) ALUM. TUBE OPTIONAL
- ⑦ 1" x .125 (6061) FLAT ALUM. BAR
- ⑧ DOW 995 PERIMETER SEALANT
- ⑨ .236 DEFENSELITE

3 SILL
ARCH. DETAIL REF.:
ARCH. SHEET REF.:

DEFENSELITE[®]