



"SS3-02-4R" END CAPS
("SS3-02-4L" OPP. HAND)



"SS3-02-1" EAVE TRIM

"SS3-02-2" EAVE GUTTER

"SS3-02-5A" 2 PC. DOWNS

"SS3-02-5B" 2 PC. DOWNS

ERECTOR NOTES:

1. "A" & "B" DIMENSIONS VARY WITH ROOF PITCH; SEE TABLE ON OPPOSITE PAGE FOR CORRECT VALUES.
2. "C" DIMENSION VARIES DUE TO CONSTRUCTION VARIATIONS.
3. ENDS OF GUTTERS @ BUTT STRIPS TO BE FIELD CAULKED & POP RIVETED.
4. FIELD LOCATE AND MARK DOWNSPOUT LOCATION IN BOTTOM OF GUTTER. DRAW LINE FROM CORNER TO CORNER AND CUT ALONG LINES. BEND TABS DOWN AND POP RIVET INSIDE DOWNSPOUT.
4. GUTTER SIZE AND GUTTER BAR SPACING MUST BE ADJUSTED TO SUIT LOCAL WEATHER PECULIARITIES AND/OR TO ACCOMMODATE LONG ROOF SLOPES.
5. FIELD FABRICATE ELBOWS FROM 10'-0" SECTIONS OF DOWNSPOUTS.

BOX 515 RAILROAD STREET
SANDY LAKE, PENNSYLVANIA 16145-0515
PHONE: 800-245-0396 ° FAX: 724-376-3864

"Fss-316" Standing Seam
Details

DRAWN BY: RW
CHECKED BY: CANON

DATE: 8/31/00
DATE:

Eave w/ Gutter
Detail

DRAWING NO.
FSS316-10