



SPECIFICATIONS

- UNIT SIZE - 50 CM X 50 CM X 2.5 CM
(20" X 20" X 1")
- AVAILABLE IN 9 STANDARD ROLL SIZES
- UNIT WEIGHT - 510 GRAMS (18 OZ.)
OR 2.0 KG (4.5 POUNDS)
- STRENGTH - 402 KG/CM (5720 PSI)
- COLOR - BLACK (STANDARD)
- RESIN - HDPE (WITH SOME POST-CONSUMER RECYCLED CONTENT)

PLAN

- GRASSPAVE2 SQUARES
- ADJACENT GRASSPAVE2 SQUARES

SEE ENLARGEMENT BELOW

HYDROGROW MIX BELOW RING
SUPPLIED FREE BY MANUFACTURER

RINGS FILLED WITH CONCRETE SAND (CLEAN, SHARP SAND)

VARIES AS PER LOADING REQUIREMENTS
- COMPACTED SANDY GRAVEL ROAD BASE
95% MODIFIED PROCTOR DENSITY
- 6 INCHES TO 12 INCHES
(DEPTH OF BASE COURSE TO BE DETERMINED BY ON-SITE ENGINEER)

COMPACTED SUBGRADE,

SECTION

- TOP OF GRASS ROOT MASS 6 MM (1/4") ABOVE TOP OF RING
- GRASSPAVE2 ATTACH WITH SNAP-FIT FASTENERS
- ROOT MASS TO FILL GRASSPAVE2
- COMPACTED SANDY GRAVEL BASE COURSE

ENLARGEMENT

NOTE: GRASS/PLANT TYPES SHALL BE SPECIFIED BY A LANDSCAPE ARCHITECT OR LANDSCAPE DESIGNER.

TYPICAL GRASSPAVE2 DETAIL

CHOOSE THIS PRODUCT FOR REINFORCING GRASS WEARING SURFACES