

C1100-XR

SCALE 1:4

TOP	TOP ASSEMBLY		ANSI/ASME			BODY HEIGHT					
ASSEMBLY	TZULTA	ADJUSTMENT		RATING		PIPE	ND	PUSH	THREADED	INSIDE	PVC/ABS
DIAMETER	MIN	MAX				SIZE	HUB	□N(P)	(T)	CAULK (X)	(-30/-31)
5″(127) 0.5	0.5"(13)	1.25"(32)	2000	TO 4.999LBS	L DC ND/ 1	2"(51)	2.75"(70)	3.375"(86)	2.25"(57)	3.75"(95)	2.94"(75)
					FR2 MR(-1)	3"(76)	2.75"(70)	3.375"(86)	2.625"(67)	3.75"(95)	3.75"(95)
				ТП 74991	_BS_SS(-3)	4"(102)	2.75"(70)	3.375"(86)	2.625"(67)	3.75"(95)	3.75"(95)
						5"(127)	3.25"(83)		2.625"(67)	3.75"(95)	
			5000	TD 7499LBS	_BS_DI(-4)	6"(152)	3.25"(83)				

1	MIFA	FOR CATALOGUE USE ONLY			
	SCALE : 1 : 4	in/[mm]	GENERAL TOLERANCE : LINEAR : N/A	P/N :	C1100-XR
	SHEET: 1 OF 1	A5	ANGULAR: N/A UNLESS OTHERWISE SPECIFIED	REV:	0