



**NOTES:**

- ROUGH OPENING MUST BE PROPERLY TREATED PRIOR TO PAN FLASHING INSTALLATION. SEE DETAIL AWB-05, AWB-06 OR AWB-07.
- INSTALL GE ELEMEX 5000 LIQUID FLASHING AS DEPICTED ONTO THE SILL AND JAMB TO ENSURE CONTINUITY OF THE AIR BARRIER.
- INSTALL PAN FLASHING INTO THE WET LIQUID FLASHING. REMOVE EXCESS LIQUID FLASHING AS REQUIRED.
- ENSURE GE ELEMEX 5000 LIQUID FLASHING IS INSTALLED A MINIMUM 2" (50 MM) ONTO PAN FLASHING VERTICAL LEG.
- GE RF100 REINFORCING FABRIC EMBEDDED IN GE ELEMEX 2600 AWB OR GE ULTRASPAN® UST2200 SILICONE TRANSITION SHEET EMBEDDED IN GE ELEMEX 5000 LIQUID FLASHING MAY ALSO BE UTILIZED TO TIE INTO PAN FLASHING.
- IT IS RECOMMENDED TO CHECK ADHESION OF GE PRODUCTS TO PAN FLASHING PRIOR TO USE. GE SS80 PRIMER CAN BE USED IF NEEDED.
- SEE GE ELEMEX 2600 AWB DATA SHEET FOR LIST OF ADDITIONAL ACCEPTABLE GE SEALANTS/LIQUID FLASHING.

**PAN FLASHING**

**GE ELEMEX® 2600 AIR AND WATER-RESISTIVE BARRIER SYSTEM**

**DETAIL #:** AWB-12

THE ABOVE DETAIL IS FOR ILLUSTRATION PURPOSES ONLY. IT IS INTENDED AS A GUIDELINE TO ASSIST MOMENTIVE PRODUCT USERS IN DEVELOPING PROJECT SPECIFIC DETAILS. CONSULT APPROPRIATE SPECIFICATION DOCUMENTS, DATA SHEETS, BUILDING CODES AND ANY OTHER INFORMATION DEEMED NECESSARY FOR SPECIFIC REQUIREMENTS. MOMENTIVE PRODUCT USERS ARE RESPONSIBLE FOR DETERMINING THE SUITABILITY OF MOMENTIVE PRODUCTS FOR THE PARTICULAR APPLICATION AND ALL RELATED PROJECT DETAILS. MOMENTIVE MAKES NO WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OF ITS PRODUCTS IN ANY USER'S APPLICATION. ANY SALE OF PRODUCTS OR DELIVERY OF CUSTOMER SUPPORT AND ADVICE BY MOMENTIVE PERFORMANCE MATERIALS INC. AND/OR ANY OF ITS AFFILIATES ("MOMENTIVE") IS MADE EXCLUSIVELY UNDER MOMENTIVE'S STANDARD CONDITIONS OF SALE, WHICH ARE AVAILABLE AT [WWW.GE.COM/SILICONES](http://WWW.GE.COM/SILICONES).

**SCALE:** N.T.S.

**DATE:** 2017-03-27