



NOTES:

- APPLY GE ELEMAX 5000 LIQUID FLASHING OVER FASTENER HEAD TO ENSURE A WATERTIGHT SEAL IS ACHIEVED.
- CONSULT BRICK TIE/ANCHOR MANUFACTURER FOR PROPER INSTALLATION INSTRUCTIONS.
- SEE GE ELEMAX 2600 AWB DATA SHEET FOR LIST OF ADDITIONAL ACCEPTABLE GE SEALANTS/LIQUID FLASHING.

**BRICK TIE/ANCHOR INSTALLED PRIOR TO GE ELEMAX 2600 AWB
GE ELEMAX® 2600 AIR AND WATER-RESISTIVE BARRIER SYSTEM**

DETAIL #: **AWB-21**

THE ABOVE DETAIL IS FOR ILLUSTRATION PURPOSES ONLY. IT IS INTENDED AS A GUIDELINE TO ASSIST MOMENTIVE PRODUCT USERS IN DEVELOPING PROJECT SPECIFIC DETAILS. CONSULT APPROPRIATE SPECIFICATION DOCUMENTS, DATA SHEETS, BUILDING CODES AND ANY OTHER INFORMATION DEEMED NECESSARY FOR SPECIFIC REQUIREMENTS. MOMENTIVE PRODUCT USERS ARE RESPONSIBLE FOR DETERMINING THE SUITABILITY OF MOMENTIVE PRODUCTS FOR THE PARTICULAR APPLICATION AND ALL RELATED PROJECT DETAILS. MOMENTIVE MAKES NO WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OF ITS PRODUCTS IN ANY USER'S APPLICATION. ANY SALE OF PRODUCTS OR DELIVERY OF CUSTOMER SUPPORT AND ADVICE BY MOMENTIVE PERFORMANCE MATERIALS INC. AND/OR ANY OF ITS AFFILIATES ("MOMENTIVE") IS MADE EXCLUSIVELY UNDER MOMENTIVE'S STANDARD CONDITIONS OF SALE, WHICH ARE AVAILABLE AT WWW.GE.COM/SILICONES.

SCALE: **N.T.S.**

DATE: **2017-03-27**