



NOTES:

- ENSURE SURFACE IS DRY, CLEAN AND FREE OF DIRT, DEBRIS AND CONTAMINANTS.
- IF A NON-FOIL FACED SELF-ADHERING MEMBRANE IS UTILIZED THE USE OF GE SS80 PRIMER MAY BE REQUIRED PRIOR TO THE APPLICATION OF GE MATERIALS. A FIELD ADHESION TEST SHOULD BE PERFORMED TO VERIFY IF THE USE OF PRIMER IS NECESSARY.
- IF A SELF-ADHERING MEMBRANE WITH AN ASPHALT BASED ADHESIVE IS UTILIZED DISCOLORATION MAY OCCUR WHERE GE PRODUCTS COME INTO CONTACT WITH THE ASPHALT. THIS DISCOLORATION IS AESTHETIC ONLY AND DOES NOT AFFECT THE PERFORMANCE OF GE PRODUCTS.
- SEE GE ELEMEX 2600 AWB DATA SHEET FOR LIST OF ADDITIONAL ACCEPTABLE GE SEALANTS/LIQUID FLASHING.

**SELF-ADHERING MEMBRANE TIE IN-METHOD A
GE ELEMEX® 2600 AIR AND WATER-RESISTIVE BARRIER SYSTEM**

DETAIL #: AWB-26

THE ABOVE DETAIL IS FOR ILLUSTRATION PURPOSES ONLY. IT IS INTENDED AS A GUIDELINE TO ASSIST MOMENTIVE PRODUCT USERS IN DEVELOPING PROJECT SPECIFIC DETAILS. CONSULT APPROPRIATE SPECIFICATION DOCUMENTS, DATA SHEETS, BUILDING CODES AND ANY OTHER INFORMATION DEEMED NECESSARY FOR SPECIFIC REQUIREMENTS. MOMENTIVE PRODUCT USERS ARE RESPONSIBLE FOR DETERMINING THE SUITABILITY OF MOMENTIVE PRODUCTS FOR THE PARTICULAR APPLICATION AND ALL RELATED PROJECT DETAILS. MOMENTIVE MAKES NO WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OF ITS PRODUCTS IN ANY USER'S APPLICATION. ANY SALE OF PRODUCTS OR DELIVERY OF CUSTOMER SUPPORT AND ADVICE BY MOMENTIVE PERFORMANCE MATERIALS INC. AND/OR ANY OF ITS AFFILIATES ("MOMENTIVE") IS MADE EXCLUSIVELY UNDER MOMENTIVE'S STANDARD CONDITIONS OF SALE, WHICH ARE AVAILABLE AT WWW.GE.COM/SILICONES.

SCALE: N.T.S.

DATE: 2017-03-27