## CORNER BEAD

PRODUCT NUMBER	DIMENSIONS/DESCRIPTIONS	PIECES PER BOX
209	DRYWALL CORNER BEAD 1 1/4" X 1 1/4" FLANGE	100

8' & 10' LENGTHS

APPLICATION: 209

TO BE USED ON ALL OUTSIDE CORNERS. RUST AND IMPACT RESISTANT. TAPERED LEGS ARE PERFORATED AND STRIATED FOR BETTER ADHESION; ELIMINATES THE NEED TO TAPE THE FLANGE. PREVENTS ELECTROLYSIS. 8' & 10' LENGTHS

## SPECIFICATION:

CORNER BEAD SHALL BE PLASTIC COMPONENTS, INC. # 209. ALL DRYWALL ACCESSORIES SHALL CONFORM TO ASTM STANDARDS D3678-97 AND C1047-99 AND D4216-99. FINISH COMPATIBLE WITH DRYWALL MUD AND ALL PAINT FINISHES. THEY SHALL BE USED WHERE SPECIFIED BY THE ARCHITECT AND INSTALLED PER INDUSTRY STANDARDS AND MANUFACTURER'S INSTRUCTIONS.

## ARCH CORNER BEAD

PRODUCT NUMBER	DIMENSIONS/DESCRIPTIONS	PIECES PER BOX
209A	DRYWALL CORNER BEAD 1 1/4" X 1 1/4" FLANGE ONE FLANGE SLOTTED.	100

8' & 10' LENGTHS

APPLICATION: 209A

TO BE USED WHERE A CURVE OR ARCH IS FORMED. PRE—SLOTTED FLANGE ALLOWS FOR PERFECT ARCHES. TAPERED FLANGES ARE PERFORATED AND STRIATED FOR BETTER ADHESION; ELIMINATES THE NEED TO TAPE THE FLANGE. 8' & 10' LENGTHS

## SPECIFICATION:

ARCH BEAD SHALL BE PLASTIC COMPONENTS, INC. # 209A. ALL DRYWALL ACCESSORIES SHALL CONFORM TO ASTM STANDARDS D3678-97 AND C1047-99 AND D4216-99. FINISH COMPATIBLE WITH DRYWALL MUD AND ALL PAINT FINISHES. THEY SHALL BE USED WHERE SPECIFIED BY THE ARCHITECT AND INSTALLED PER INDUSTRY STANDARDS AND MANUFACTURER'S INSTRUCTIONS





