


INSTALLATION REQUIREMENTS PER USPS STD-4C

1. AT LEAST ONE CUSTOMER MAILBOX COMPARTMENT SHALL BE POSITIONED LESS THAN 48" ABOVE FINISHED FLOOR (AFF).
2. NO PARCEL LOCKER COMPARTMENT (INTERIOR BOTTOM SHELF) SHALL BE POSITIONED LESS THAN 15" AFF.
3. NO CUSTOMER MAILBOX LOCK SHALL BE LOCATED MORE THAN 67" AFF.
4. NO CUSTOMER MAILBOX COMPARTMENT (INTERIOR BOTTOM SHELF) SHALL BE POSITIONED LESS THAN 28" AFF.
5. THE USPS ARROW LOCK IN THE CARRIER ACCESS DOOR SHALL BE LOCATED BETWEEN 36" AND 48" AFF.

*NOTE: THE BOTTOM EDGE OF THE ROUGH OPENING MUST BE AT 14" AFF IN ORDER TO COMPLY WITH THE REQUIREMENTS ABOVE.



REV. 1

DRAWN AE	 email: engineering@mailboxes.com	1010 E. 62nd Street Los Angeles, CA 90001 Phone: (800) 624-5269 Fax: (800) 624-5299	4C STANDARD HORIZONTAL MAILBOXES 3700 SERIES FRONT LOADING AVAILABLE FOR USPS ACCESS OR PRIVATE ACCESS	(20) MB1 MAILBOXES (1) OM2 OUTGOING MAIL COMPARTMENT (2) PL4.5 PARCEL LOCKERS	MODEL 3716D-20 DRAWING NO. CAD_3716D-20FL
DATE 08/20/2015					
CAD FILE SCALE 1 : 1					