


SURFACEMAX P.O. BOX 577 EAST AURORA, NY 14052 PHONE: (716) 652-2039 FAX: (716) 805-1001

www.playandpark.com/products/surfacing

- WEAR COURSE - 1/2" MINIMUM THICKNESS OVER PRIMED SUB-BASE. NEW ASPHALT MUST BE POWER WASHED PRIOR TO PRIMING 1 1/2" - 45° EDGE BEVEL AGAINST PRIMED - CONCRETE BORDER TO PREVENT SHRINKING



SUB-BASE OPTIONS PER ADA GUIDELINES: (1) CONCRETE - MINIMUM OF 3 - 4" AT A MINIMUM 2500 PSI. MUST CURE FOR 7 DAYS PRIOR TO RUBBERIZED CUSHION LAYER. MUST CURE FOR 28 DAYS IF WEAR COURSE IS TO BE APPLIED DIRECTLY TO CONCRETE SURFACE. (2) ASPHALT - MUST CURE A MINIMUM OF 14 DAYS, POWER WASHED

CONCRETE BORDER

SECTION VIEW

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5251-044.



5251-044 REVISION DATE 15/11/2023