



PERSPECTIVE



FRONT ELEVATION



SIDE ELEVATION

#### DESCRIPTION

THESE TILES LOCK TOGETHER TO CREATE A FLOATING FLOOR TYPE EFFECT TO RESIST DEFORMING IN CHANGING WEATHER CONDITIONS. IDEAL FOR INDOOR OR OUTDOOR PLAYGROUND FLOORING. THESE TILES ARE EASY TO INSTALL AND REQUIRE A LIMITED ADHESIVE APPLICATION TO AVOID INSTALLATION MESS. IMPACT ATTENUATING AT 4', 6' OR 8', THESE TILES ARE DESIGNED TO EXCEED REQUIREMENTS FOR IMPACT ATTENUATION. THEY SCORED 750 ON THE HEAD INJURY CRITERIA SCALE - 25% UNDER THE FEDERAL GUIDELINES.

#### BENEFITS:

AVAILABLE IN A WIDE VARIETY OF COLORS

CREATE CHECKBOARD PATTERNS OR OTHER BASIC DESIGNS


LOCKING TECHNOLOGY MAKES INSTALLATION EASY, PREVENTS TILE LIFTING, AND ENSURES A SNUG FIT FOR YEARS TO COME

#### SPECIFICATIONS:

- 10 YEAR LIMITED WARRANTY INCLUDING ASTM F1292-09 ATTENUATION CRITERIA
- VARIOUS THICKNESSES AVAILABLE TO MATCH YOUR PLAYGROUND'S FALL HEIGHT
- TILE ACCESSORIES SUCH AS CORNERS, RAMPS, GLUE, AND CONNECTORS AVAILABLE
- USA MANUFACTURING AND MATERIALS
- STRUCTURAL BASE HELPS PREVENT TILE SAGGING

#### NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT [www.CADdetails.com/info](http://www.CADdetails.com/info) AND ENTER REFERENCE NUMBER 5251-080.



**SURFACEMAX RUBBER TILES**

U-LOCK