9.1 MECHANICAL TERMINATION WITH COUNTER FLASHING





NOTES:

1. APPLY ON HARD SMOOTH SURFACE ONLY; NOT FOR USE ON EXPOSED WOOD.
2. DO NOT WRAP TERMINATION BAR AROUND CORNERS.
3. DETAIL 9.5 MUST BE USED AT VERTICAL JOINTS IN PANEL WALLS.

MAXIMUM WARRANTY: 30 YEARS

9.2 SHEET METAL COPING BY OTHERS





NOTE:

1. MEMBRANE MUST BE EXTENDED TO CORNERS TO PROVIDE COMPLETE COVERAGE OF THE TOP WALL SURFACE.

MAXIMUM WARRANTY: 30 YEARS

9.3 COUNTER FLASHING TERMINATION



NOTE:

1. WHEN MECHANICAL FASTENERS ARE USED TO PENETRATE THE METAL COUNTER-FLASHING, USE EPDM WASHERS, APPLY WATER CUT-OFF MASTIC UNDER THE COUNTER-FLASHING OR CAULK THE FASTENER HEADS.

MAXIMUM WARRANTY: 10 YEARS

9.4 MECHANICAL TERMINATION





NOTES:

1. APPLY ON HARD SMOOTH SURFACE ONLY; NOT FOR USE ON EXPOSED WOOD.
2. DO NOT WRAP TERMINATION BAR AROUND CORNERS.
3. DETAIL 9.5 MUST BE USED AT VERTICAL JOINTS IN PANEL WALLS.

MAXIMUM WARRANTY: 20 YEARS

— — APPLICABLE BONDING ADHESIVE
MAXIMUM WARRANTY: 10-30 YEARS

xxx WATER CUT-OFF MASTIC- MUST BE HELD UNDER CONSTANT COMPRESSION.

VERSICO ROOFING SYSTEMS
© 2022 VERSICO

MEMBRANE TERMINATIONS
PAGE 1 OF 2

EPDM MEMBRANE
APPROVED SUBSTRATE
0 SEE NOTE(S)

THERMOSET ROOFING SYSTEM
VGC-9.0A