

- 1. SLEEPER MUST BE LARGE ENOUGH TO SUPPORT WEIGHT OF EQUIPMENT WITHOUT INDENTING INSULATION. EXTEND SLEEPER OUT AS REQUIRED BY STRUCTURAL ENGINEER TO DISTRIBUTE SUBJECT LOAD OR AT LEAST EXTEND OUT MIN. 3" (7.5cm).
- 2. ENSURE SCREW/ANCHOR HEADS IN TOP SURFACE OF WOOD BLOCKING ARE RECESSED TO PROTECT MEMBRANE.


- 3. SLEEPER NOT REQUIRED UNDER CONDUIT OR PIPE SUPPORTS.
- 4. CONSULT STRUCTURAL
  ENGINEER AND/OR SPECIFIER TO
  AVOID WATER PONDING DUE TO
  DECK DEFLECTION.
- 5. RAISE CONDUIT AND PIPES ABOVE THE REGIONAL SNOW LINE WHEN SLOPE OF THE ROOF CAN LEAD TO SLIDING SNOW.

DIMENSIONS		cm	
$\bigcirc$	3"	7.5	MIN. ALL SIDES
B	8"	20	

WELD



SLEEPER DETAIL



THERMOPLASTIC ROOFING SYSTEM

TPC-24