



Home Innovation
NGBS GREEN CERTIFIED™

THIS IS TO SIGNIFY THAT THE FOLLOWING
PRODUCTS FOR RESIDENTIAL CONSTRUCTION

VIANCE PRESERVE (ACQ) PRESSURE TREATED LUMBER

MANUFACTURED BY

VIANCE LLC

HAVE BEEN CERTIFIED FOR POINTS TOWARD NGBS GREEN CERTIFICATION TO
THE ICC 700 NATIONAL GREEN BUILDING STANDARD AS DETAILED IN NGBS
GREEN CERTIFIED PRODUCT REPORT #NGBSGCP-000103.

Thomas M. Kenney, P.E. – VP Research & Engineering

January 15, 2010

Approval Date

December 31, 2020

Expiration Date

CERTIFICATE #000103

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certified Product Report #NGBSGCP-000103

Products: Viance Preserve (ACQ) Pressure Treated Lumber

Manufacturer: Viance LLC

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2012 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS
2012 NGBS 503.2(4)	Erosion reduced through use of terracing, retaining walls, landscaping and restabilization.	5	Retaining walls built with this product must be an integral part of the installed landscape plan designed to limit long-term erosion.
2012 NGBS 602.1.6	Termite-resistant materials are used in portions of the building.	2-6	To earn 2 points, product is used in conjunction with other termite-resistant materials for the first 2' of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.

2015 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS
2015 NGBS 503.2(4)	Erosion reduced through use of terracing, retaining walls, landscaping and restabilization.	6	Retaining walls built with this product must be an integral part of the installed landscape plan designed to limit long-term erosion.
2015 NGBS 602.1.6	Termite-resistant materials are used in portions of the building. . .	2-6	To earn 2 points, product is used in conjunction with other termite-resistant materials for the first 2' of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. Four points are awarded when used in the first 3' in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.