

TECHNICAL DATA SHEET

**DESCRIPTION**

A-20 is a woven UV stabilized HDPE scrim with a polyethylene coating on both sides.

**PHYSICAL PROPERTIES AND TYPICAL VALUES**

PROPERTY	ASTM TEST METHOD	U.S. VALUE	METRIC VALUE
Weight	D-2103	35 LB/1000 FT <sup>2</sup>	17.1 KG/100 M <sup>2</sup>
Thickness	D-2103	6 MIL	0.152 MM
Tensile Grab Strength	D-751	195 LBS	865 N
Tongue Tear	D-2261	74 LBF	330 N

**AVAILABLE COLORS**

Clear or Black/White

**OUR CUSTOMERS DON'T JUST** *cover their business,*  
**➔ THEY PROTECT IT**



**REEF INDUSTRIES, INC.**  
 9209 Almeda Genoa Rd. • Houston, Texas 77075  
 P: 713.507.4251 • F: 713.507.4295  
 E-mail: [ri@reefindustries.com](mailto:ri@reefindustries.com) • [www.reefindustries.com](http://www.reefindustries.com)

**TOLLFREE 1.800.231.6074**

The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, expressed or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.