




Model 3242

Ribbed

chiohd.com

1485 Sunrise Dr.
Arthur, IL 61911
Phone: (800) 677-2650

STANDARD FEATURES Standard up to 24'2" x 20'0". *Consult with C.H.I. up to 34'2" wide or 32'0" tall.*



- Ribbed appearance
- 2" thick sections
- Tongue and groove section joints
- 24 gauge smooth face steel
- 18", 21", and 24" section heights
- End stiles - 18 gauge riveted
- 1-1/2" CFC free polystyrene vinyl back insulation
- 27 gauge steel backer with plastic retainers
- Center stiles - 18 gauge with painted face rivets
- Center stile in top section [all widths]
- U-shaped bottom astragal with aluminum retainer
- Available in 3" height increments - sandstone, brown, black, and gray not available for 6'3", 6'6", 6'9", 8'3", 8'6", and 10'3" heights
- R-Value¹ = 8.00

COLORS

WHITE, SANDSTONE, BROWN, BLACK, GRAY, POWDER COAT²

TRACK

- 15" radius bracket mount track
- Up to 8'0" height - 17 gauge 2" track
- 8'3" to 10'0" height - 16 gauge 2" track
- 10'3" to 14'0" height - 14 gauge 2" track
- Over 14'0" height - 12 gauge 3" track
- Vertical track to be mounted with track brackets, clip mount angle, or continuous jamb angle.
- Horizontal track to be reinforced with 13 gauge angle according to door size and weight.

HARDWARE

- Graduated hinges - 14 gauge
- Top fixtures - 12 gauge
- Bottom fixtures - 13 gauge
- Over 16'2" width - Double end hinges
- Rollers - 10 ball bearing
 - Case hardened steel tire
 - Solid shaft

SPRING COUNTERBALANCE

Torsion springs mounted on a cross header shaft supported by galvanized steel ball-bearing end plates and center bracket[s]. Springs are custom-designed for exact door weight, size, and trajectory according to current ANSI/DASMA 102 standards for a minimum of 10,000 cycles. Counterbalanced with galvanized aircraft quality cables secured to the bottom of the door. 20,000, 50,000, and 100,000 cycle springs are available as an upgrade option.

STRUTTING

Galvanized strutting provided according to door size and design.

SECURITY OPTIONS *No lock is standard*

- Inside slide lock - Torsion spring required
- Outside center lock - Not available with 3" track
- Double lock bar - Not available with 3" track - Not available with doors over 18' wide

GLAZING *3/4" Insulated glass*

- Glazing Types - Plain [DSB]
 - Tinted
 - Tempered
- Full-View Aluminum section
- Glazing Dimensions - 24" x 6"
 - 24" x 12"
 - 34" x 16"

FRAMING / INSTALLATION

Torsion spring mounting pads, jamb plates, header plates, and associated track system hangers shall be furnished by other than C.H.I. All installation quality and workmanship is responsibility of contractor and is to be executed in accordance with C.H.I. installation instructions, local and state building codes and work site safety regulations.

¹R-value calculation is in accordance with ANSI/DASMA 163 and ASTM C518 standards.

²Maximum width of Powder Coat is 20'2"

³Calculations do not account for options including but not limited to windows and/or exhaust ports.

⁴18" will only be available on white and powder coating.



windloadocfinder.chiohd.com

All information presented is based on the specifications and features available at the time the document was created and is subject to change without notice.

07-JUL 2024-04 / ©2024 C.H.I. Overhead Doors - a NUCOR® company