This document has been prepared in accordance with the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (HCS), 29 Code of Federal Regulations § 1910.1200(g).

SECTION I	IDENTIFICATION		
	PRODUCT IDENTIFICATION		
	Product Name:	Thin Brick and Quarry Tile	
	RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE		
	Product Use:	Thin Brick and Quarry Tile are products used as coverings for floors and walls.	
	MANUFACTURER INFORMATION		
	Name:	Ironrock Capital Inc.	
	Address:	1201 Millerton Street SE Canton, Ohio 44707	
	Telephone Number:	330-484-4887	
	EMERGENCY TELEPHONE NUMBER		
	Emergency Telephone Number:	330-484-4887	
SECTION II	HAZARD IDENTIFICATION		
	CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR 1910.1200		
	Skin Irritation:	Not Available	
	Serious Eye Damage:	Not Available	
	Skin Sensitization:	Not Available	
	GHS Classification (Global Harmonized Standard Classification):		
	Specific Target Organ Toxicity Single Exposure:	Respiratory tract irritation – Category 3 (H335)	
	Specific Target Organ Toxicity Repeated Exposure:	Category 1A (H372)	
	Carcinogenicity:	Category 1A (H350)	
	SIGNAL WORD (GHS-US)		
	DANGER		
	HAZARD STATEMENTS (GHS-US)		
	May cause cancer (inhalation) May cause respiratory irritation Causes damage to organs (lung/respiratory) through prolonged or repeated (inhalation)		
	HAZARD SYMBOLS (GHS-US)		

Ironrock Capital Inc.

PRECAUTIONARY STATEMENTS (GHS-US)

Do not handle until all safety precautions have been read and understood. (P202) Do not breathe dust/spray. (P260 & P261) Wash skin thoroughly after handling. (P264) Do not eat, drink, or smoke when using this product. (P270) Wear protective gloves, protective clothing, eye protection, face protection. (P280)

HAZARDS NOT OTHERWISE CLASSIFIED

Caution should be used when sawing this product as dust may be released. This dust may contain respirable Crystalline Silica (Quartz). It is recommended that a wet saw be used.

UNKNOWN ACUTE TOXICITY

Not Available

SECTION III COMPOSITION/INFORMATION ON INGREDIENTS

Thin Brick and Quarry Tile are composed of mixtures of naturally occurring clay and shales fired to at least 1100 degrees C.

Chemical Name:	Respirable Crystalline Silica
Common Names and Synonyms:	Quartz
CAS Number:	14808-60-7
Estimated % by Weight:	20-30

SECTION IV FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

Skin Contact:	Wash thoroughly after working with tiles.
Eye Contact:	Flush eyes with water if dust gets in eyes.
Inhalation:	Heavy contamination with dust may cause respiratory irritation to the nose and throat. Remove the affected person from the area to fresh air. To avoid inhalation risks, do not dry cut this product. Use a wet saw.
Ingestion:	Not applicable for intact tiles.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

We recommend wet cutting during the installation process. The following applies to the product only if it is dry cut or sanded in such a way that significant airborne dusts containing respirable crystalline silica may be generated: Exposure may aggravate pre-existing eye, skin, or respiratory conditions. May cause respiratory irritation. May cause cancer. May cause damage to lungs through prolonged or repeated exposure.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Not Available

SECTION V FIRE-FIGHTING MEASURES

These products are not flammable. No fire or explosion hazards exist.

SUITABLE AND UNSUITABLE EXTINGUISHING MEDIA

Not Available

SPECIFIC HAZARDS ARISING FROM CHEMICAL

Not Available

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS

Not Available

SECTION VI ACCIDENTAL RELEASE MEASURES

These products do not release hazardous material.

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use individual protection recommended in Section VIII.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Use wet cutting methods to avoid creating excessive dust. Clean up dust with a vacuum system with a High-Efficiency Particulate (HEPA) Air Filter vacuum or damp sweeping.

SECTION VII HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

When cutting or grinding, use a wet method. If a wet method is not available, use local dust collection or ventilation. Use a respirator when cutting or grinding.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Shelf life is unlimited. Comply with applicable regulations.

SECTION VIII EXPOSURE CONTROL/PERSONAL PROTECTION

EXPOSURE LIMITS FOR CRYSTALLINE SILICA

OSHA Permissible Exposure Limit:	50 μg/m ³ (micrograms per cubic meter of air) measured as an 8-hour workday (time weighted average or "TWA").
ACGIH Threshold Limit Value:	0.025 mg/m ³ (respirable particulate matter)
EXPOSURE CONTROLS	

 Engineering Controls:
 Use adequate ventilation to keep dust exposure below recommended levels when cutting. Avoid inhalation of dust. Wet cutting methods and exposure control methods set forth in Table 1 of 29 CFR § 1926.1153 are recommended.

INDIVIDUAL PROTECTION MEASURES

Eye Protection:	Use dustproof goggles or safety glasses with side shields when cutting.
Respiratory Protection:	Use a properly fitted NIOSH/MSHA approved particulate respirator when cutting.
General Health and Safety Measures	· Personal protection information in Section VIII is based on general information for

General Health and Safety Measures: Personal protection information in Section VIII is based on general information for normal uses and conditions. Where special or unusual uses or conditions exist, it is suggested that the expert assistance of an industrial hygienist or other qualified professional be sought.

SECTION IX PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE (PHYSICAL STATE, COLOR, etc.)

Thin Brick and Quarry Tile is a solid, non-flammable, odorless product. It comes in various colors.

ODOR

Thin Brick and Quarry Tile is odorless.

ODOR THRESHOLD

Not Available

pН

Not Available

MELTING POINT/FREEZING POINT

Not Available

INITIAL BOILING POINT AND BOILING RANGE

Not Available

FLASH POINT

Not Available

EVAPORATION RATE

Not Available

FLAMMABILITY (SOLID, GAS)

Thin Brick and Quarry Tile is solid, non-flammable. It will not ignite or explode.

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS

Not Available

VAPOR PRESSURE

Not Available

VAPOR DENSITY

Not Available

RELATIVE DENSITY

Not Available

SOLUBILIY

Thin Brick and Quarry Tile is not soluble in water, however it should not be used near or contacted with Hydrofluoric acid as it may leach heavy metal residues

PARTITION COEFFICIENT: N-OCTANOL/WATER

Not Available

AUTO-IGNITION TEMPERATURE

Not Available

DECOMPOSITION TEMPERATURE

Not Available

VISCOSITY

SECTION X Not Available STABILITY AND REACTIVITY

REACTIVITY

No dangerous reaction known under conditions of normal use.

CHEMICAL STABILITY

Stable.

POSSIBILITY OF HAZARDOUS REACTION

No dangerous reaction known under conditions of normal use.

CONDITIONS TO AVOID

Avoid contact with Hydrofluoric acid.

INCOMPATIBLE MATERIALS

Hydrofluoric acid.

HAZARDOUS DECOMPOSITION PRODUCTS

Not Available

SECTION XI TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE

Skin contact, eye contact, inhalation, ingestion.

SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS

Skin Contact:	Dust or occasional contamination on the skin will cause no adverse effects.	
Eye Contact:	Entry of dust or chips into the eyes as a foreign body will cause local irritation.	
Inhalation:	Heavy contamination with dust may cause respiratory irritation to nose and throat. Repeated exposure by inhalation may cause a serious chronic effect which could lead to silicosis, a serious lung disease. The onset of silicosis is usually slow and lung damage may occur without symptoms or signs of ill health. Silicosis can develop to a more serious degree even after exposure has ceased and may lead to other diseases including heart disease. Development of silicosis may increase the risk of lung cancer. To minimize the risk, caution should be taken when sawing or during demolition of Thin Brick and Quarry Tile. Wet cutting, proper ventilation, and the use of a properly fitted NIOSH/MSHA approved particulate respirator is recommended.	
Ingestion:	Unlikely, but non-toxic if swallowed.	
DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE		
Short-Term Exposure:	Not Available	
Long-Term Exposure:	The dust generated from cutting Thin Brick and Quarry Tile may release respirable Crystalline Silica, a known carcinogen, and prolonged or repeated inhalation of dust may lead to silicosis and cancer.	
	NIGITY.	

NUMERICAL MEASURES OF TOXICITY

Acute Toxicity:

Not Available

NATIONAL TOXICOLOGY PROGRAM REPORT ON CARCINOGENS

Carcinogenicity of Quartz:	 National Toxicology Program Status Known Human Carcinogens International Agency for Research on Cancer Status 1 – The agent (mixture) is carcinogenic to humans OSHA OSHA Hazard Communication Carcinogen List
NPT:	Yes
IARC Monographs:	Yes
OSHA:	Yes

SECTION XII ECOLOGICAL INFORMATION

Thin Brick Quarry Tile produce no environmental hazards.

ECOTOXICITY

Not Available

PERSISTENCE AND DEGRADABILITY

Not Available

BIOACCUMULATIVE POTENTIAL

Not Available

MOBILITY IN SOIL

Not Available

OTHER ADVERSE EFFECTS

Not Available

SECTION XIII DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Waste Thin Brick and Quarry Tile should be disposed of in accordance with applicable State and Local regulations. It is not a hazardous waste under United States Environmental Protection Agency regulations.

OTHER DISPOSAL CONSIDERATIONS

Not Available

SECTION XIV TRANSPORT INFORMATION

There are no hazards in storage or shipping of Thin Brick and Quarry Tile. There are no known regulations or constraints for storing or transporting these products.

UN NUMBER

Not Regulated

UN PROPER SHIPPING NAME

Not Regulated

TRANSPORT HAZARD CLASS

Not Regulated PACKING GROUP, IF APPLICABLE

Not Regulated

ENVIRONMENTAL HAZARD

Not Available

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not Available

SPECIAL PRECAUTIONS FOR USER

Not Available

SECTION XV REGULATORY INFORMATION

SAFETY, HEALTH, AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE PRODUCT

United States: SDS prepared pursuant to the Hazard Communication Standard (29 CFR § 1910.1200)

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS

OSHA: ACGIH:	Occupational Safety and Health Administration American Conference of Governmental Industrial Hygienists
ACGIN.	Anencan confirmed of Governmental industrial hygienists Al – Confirmed human carcinogen
IARC:	International Agency for Research on Cancer
	 1 – The agent (mixture) is carcinogenic to humans
NTP:	National Toxicology Program
	Known Human Carcinogens
State Regulations:	-
-	 Massachusetts – Right To Know List
	 New Jersey – Right to Know Hazardous Substance List
	 Pennsylvania – RTK (Right to Know) List

SECTION XVI OTHER INFORMATION

Date of Preparation:	December 12, 2014
Date of Revision:	January 30, 2022