

SDS - Safety Data Sheet

Section 1. IDENTIFICATION

Product Name: PRO-STICK 37 Effective Date: 17 August 2022

Product Use: Mortar

Manufacturer Name: PROFLEX® Products, Inc.

1603 Grove Ave Haines City, FL 33844

www.Proflex.us

Emergency Phone: 877-577-6353 **Product Information:** 877-577-6353

Section 2. HAZARD(S) IDENTIFICATION

GHS Pictograms Signal Words







Signal Word: Danger

Classification of the Substance or Mixture

Skin Corr. 1A Causes severe skin burns and eye damage.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1 May cause an allergic skin reaction.

Carc. 1A May cause cancer if inhaled.

STOT SE 3 May cause respiratory irritation

STOT RE 1 Causes damage to organs through prolonged or repeated exposure if inhaled.

Hazard statements:

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H350 May cause cancer if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

8/17/2022 Product: PRO-STICK 37 Page **1** of **8**



P310 Immediately call a doctor.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see supplementary instructions on this label)
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+ P363 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local, regional, national, and

international regulations...

Other Hazards Exposure may aggravate pre-existing eye, skin, or respiratory conditions

Ingredient(s) with unknown acute toxicity (GHS-US/CA): No data available

Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances or Mixture: Not available

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification: None

List of components

Concentration		Ident. No:	Classification	Registration No:
55-75 %*	Silica Sand	CAS:14808-60-7	STOT RE 1, H372; Carc. 1A, H350	_
15-45 %*	Cement, Portland,		•	
	chemicals	CAS:65997-15-1	STOT SE 3, H335; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1A, H314	
30-1 %*	Limestone	CAS: 1317-65-3	Not Classified	
10-0.5 %*	Calcium oxide	CAS: 1305-78-8	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402	

^{*}Means that the component will fall into one of the ranges specified due to batch-to-batch variability and to protect Confidential Business Information.

SECTION 4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact: Wash with plenty of water and soap. In case of eyes contact: Wash immediately with water.

In case of Ingestion: Do not induce vomiting, get medical attention showing the SDS and the hazard

label.

In case of Inhalation: Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed:

Not available

Indication of any immediate medical attention and special treatment needed

Treatment: Not available

8/17/2022 Product: PRO-STICK 37 Page **2** of **8**



SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Water. Carbon dioxide (CO2)

Unsuitable extinguishing media: None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

Explosive properties:

Oxidizing properties:

Not available

Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Do not allow to enter into soil/subsoil.

Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning/collecting

For dry material, collect by sweeping and scooping. Transfer collected material to a container, being careful to minimize the creation of dust.

For wet material, scoop material up and transfer to an open container. Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

Allow material to dry before disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Use in well-ventilated areas. Wear impervious gloves and eye protection. Do not

mix with other chemical products, except as indicated by the manufacturers. Do not get in eyes. Do not get on skin or clothing. Do not breathe dust. Do not take

internally.

General Hygiene Advice: Use good industrial hygiene practices and wear recommended personal

protection. Launder contaminated clothing before reuse. Wash hands before

eating, drinking, or smoking.

Conditions for safe storage, including any incompatibilities

Storage: Keep out of the reach of children. Store locked up. Keep container tightly closed.

Store at room temperature and keep containers closed when not in use. Keep

dry until use.

8/17/2022 Product: PRO-STICK 37 Page **3** of **8**



SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For any substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or provincial governments.

Silica Sand (CAS: 148	808-60-7)	
USA ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 μg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m³ (respirable dust)
USA IDLH	US IDLH (mg/m³)	50 mg/m³ (respirable dust)
Cement, Portland, ch	emicals (CAS: 65997-15-1)	
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust), 5 mg/m³ (respirable dust)
USA IDLH	US IDLH (mg/m³)	5000 mg/m ³
Limestone (CAS: 131	7-65-3)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust), 5 mg/m³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust), 5 mg/m³ (respirable dust)
Calcium oxide (CAS:	1305-78-8)	
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	2 mg/m³
USA IDLH	US IDLH (mg/m³)	25 mg/m³

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Face shield.











Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosion-proof clothing.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles and face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

8/17/2022 Product: PRO-STICK 37 Page **4** of **8**



SDS - Safety Data Sheet

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Solid Powder (Gray Or White)

Odor: Cement like
Odor Threshold: Not Available

pH: 10.0 – 13 when wet

Melting point/Freezing point:

Initial boiling point and boiling range:

Flash point:

Not Available

Not Available

Evaporation rate (Water=1): Not Available

Flammability: Not Flammable/Not Combustible

Upper Flammability/Explosive Limit:

Lower Flammability/Explosive Limit:

Vapor Pressure

Vapor Density:

Relative Density:

Solubility in Water:

Not Available

Not Available

Not Available

2.0 – 3.15 g/mL

Insoluble

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

Decomposition Temperature:

Viscosity (cps):

Not Available

Not Available

Not Available

VOC Content: 0 g/L

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Stable under normal conditions

Chemical stability: Stable under normal storage conditions. Keep dry in storage.

Possibility of hazardous reactions: No dangerous reaction known under conditions of normal use

Conditions to avoid: Stable under normal conditions. Heat and Incompatible materials.

Incompatible materials: Strong acids. Strong Oxidizers.

Hazardous decomposition products: Will not spontaneously occur. Addition of water will produce caustic calcium

hydroxide, which can cause chemical burns.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects
Toxicological information of the mixture:

a) acute toxicity

Not classified. Based on available data, the classification criteria are not met

b) skin corrosion/irritation The product is classified: Skin irritation, Category 2(H315) C) serious eye damage/irritation The product is classified: Serious eye damage, Category 1(H318)

d) respiratory or skin sensitisation The product is classified: Skin Sensitization, Category 1(H317)

e) germ cell mutagenicity

Not classified. Based on available data, the classification criteria are not met

f) carcinogenicity The product is classified: Carcinogenicity, Category 1A(H350)

g) reproductive toxicity

Not classified Based on available data, the classification criteria are not met

Not classified Based on available data, the classification criteria are not met

Not classified Based on available data, the classification criteria are not met

The product is classified: Specific target organ toxicity following repeated

exposure, Category 1(H372)

j) aspiration hazard Not classified Based on available data, the classification criteria are not met

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

8/17/2022 Product: PRO-STICK 37 Page **5** of **8**



SECTION 11. TOXICOLOGICAL INFORMATION - continue

Toxicological information on main components of the mixture:

LD50 and LC50 Data:

Silica Sand (CAS: 14808-60-7)		
LD50 Oral Rat	> 5000 mg/kg	
LD50 Dermal Rat	> 5000 mg/kg	
Calcium oxide (CAS: 1305-78-8)		
LD50 Oral Rat	> 2000 mg/kg	
LD50 Dermal Rabbit	> 2500 mg/kg	

Silica Sand (CAS: 14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Ecology - General:	Not classified.
--------------------	-----------------

Calcium oxide (CAS: 1305-78-8)		
LC50 Fish 1	50.6 mg/l	
Persistence and Degradability:	Not available	
Bioaccumulative Potential:	Not available	
Calcium oxide (CAS: 1305-78-8)		
BCF Fish 1	(no bioaccumulation)	
Mobility in Soil	Not available	
Other Adverse Effects:	Not available	

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national,

territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14. TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

Land transport DOT Not regulated for transport
Sea transport IMDG Not regulated for transport
Air transport IATA / CAO Not regulated for transport

8/17/2022 Product: PRO-STICK 37 Page **6** of **8**



SECTION 15. REGULATORY INFORMATION

US Federal Regulations

SARA Section 311/312 Hazard Classes Health hazard - Specific target organ toxicity (single or repeated

exposure)

Health hazard - Carcinogenicity

Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation

Health hazard - Skin corrosion or Irritation

Silica Sand (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium oxide (CAS: 1305-78-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Cement, Portland, chemicals (CAS: 65997-15-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Limestone (CAS: 1317-65-3) Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations California Proposition 65

Chemical Name	Carcinogenicity Developmental	Female Reproductive	Male Reproductive	
(CAS No.)	Toxicity	Toxicity	Toxicity	

Silica Sand (14808-60-7)

Silica Sand (CAS: 14808-60-7)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

Χ

U.S. - Pennsylvania - RTK (Right to Know) List

Calcium Oxide (CAS: 1305-78-8)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Cement, Portland, chemicals (CAS: 65997-15-1)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Limestone (CAS: 1317-65-3)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Disclaimer: The information is furnished without warranty, representation, inducement, or license of any kind, except that it is accurate to the best of the SDS Departments' knowledge. Because use conditions and applicable laws may differ from one location to another and may change with time, Recipient is responsible for determining whether the information is appropriate for recipient's use. Since PROFLEX has no control over how this information may be ultimately used, all liability is expressly disclaimed and PROFLEX assumes no liability.

8/17/2022 Product: PRO-STICK 37 Page **7** of **8**



Section 16. Other information

Safety Data Sheet version 081622

Additional classification information

NFPA Health: 2 = Moderate

NFPA Flammability: 0 = Not Combustible

NFPA Reactivity: 0 = MinimalNFPA Special Risk: NONE



Code	Description
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

Abbreviations:

≤ Less Than or Equal To ≥ Greater Than or Equal To

ACGIH American Conference of Governmental Industrial Hygienists

BCF Bioconcentration factor

°C Celsius temperature scale

CAS: Chemical Abstract Service Number

CAO. Cargo Aircraft Only

CFR Code of Federal Regulations **CNS** Central Nervous System

DOT Department of Transportation

EC50 Effective Dose

°F Fahrenheit temperature scale Prop. Proprietary

IARC International Agency for Research on Cancer IATA International Air Transport Association IDLH Immediately Dangerous To Life or Health IMDG International Maritime Dangerous Goods code

LC50 Lethal Inhalation Concentration LD50 Lethal Dose

LEL Lower explosive limit

NA Not available

NFPA National Fire Protection Agency IOSH National Institute of Safety & Health

NTP National Toxicology Program

OSHA Occupational Safety & Health

PE Personal Protective Equipment **PEL** Permissible Exposure Limit

RCRA Resource Conservation Recovery Act

SARA Superfund Amendments and Reauthorization Act

STEL Short-term Exposure Limit

STOT RE Specific Target Organ Toxicant (repeated exposure)

STOT SE Specific Target Organ Toxicant (single exposure)

TLV Threshold Limit Value **TSCA** Toxic Substance Control Act TWA Time Weighted Average

UEP Upper explosive limit **USA** United States

VOC Volatile organic content

WHMIS Workplace Hazardous Materials Information System

8/17/2022 Product: PRO-STICK 37 Page 8 of 8