



SLU PRIMER

2022-04-05

1. PRODUCT NAME

SLU Primer

2. MANUFACTURER

PROFLEX® Products, Inc.

1603 Grove Ave.

Haines City, FL 33122

Telephone: 863-937-9623

Toll Free: 877-577-6353

Fax: 863-937-9624

Internet: www.proflex.us

3. PRODUCT DESCRIPTION

PROFLEX® SLU Primer is a liquid agent and additive that will bond concrete to concrete. SLU Primer can be used with Portland cement mixes. Using it in a cement mix can improve compressive strength, water resistance, chemical resistance, and most other physical properties of cement/sand mixes. SLU Primer should be used with PROFLEX® SLU Underlayment.

Advantages

- Used as a bonding agent, SLU Primer permits direct application of Portland cement mixes to structurally sound surfaces.
- SLU Primer improves resilience for thermal and mechanical movement.
- Greater compressive strengths are achieved when used in cement/sand mixes.

4. TECHNICAL DATA

Physical Properties

- Vinylacetate - Vinylsaceticester - terpolymer
- Not affected by alkalinity of lime or Portland cement
- PH Value 4.5
- Shear bond strength 2250 PSI

DO NOT FREEZE DURING STORAGE, APPLICATION OR CURE.

5. INSTALLATION

Surface Preparation

All surfaces should be between 40°F and 90°F, structurally sound, clean and free of all dirt, oil, grease, loose peeling paint, concrete sealers or curing compounds. Remove all dust by vacuuming.

Application

Stir well before using. Pour on substrate and spread with a broom or squeegee. Allow primer to dry approximately 2 hours.

Safety

Avoid contact with skin where possible. Wash exposed skin areas promptly with water. If mortar gets in eyes, rinse immediately and repeat. Get prompt medical attention. **Keep out of reach of children.**

6. AVAILABILITY

PROFLEX® Products are available nationwide.

To locate PROFLEX® products in your area, please contact:

Phone: 877-577-6353

Website: www.proflex.us

7. WARRANTY



SLU PRIMER

2022-04-05

PROFLEX® Products, Inc. offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical services at 877-577-6353 or visiting www.proflex.us

8. MAINTENANCE

None required, but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. TECHNICAL SERVICES

Technical assistance

Information is available by calling the Technical Support

Toll Free: 877-577-6353

Fax: 863-937-9624

Technical and safety literature: To acquire technical and safety literature, please visit our website www.proflex.us

10. FILING SYSTEM

Division 9